



Replacement Basket Filters Specification



Flat Top, Flat Bottom



Flat Top, Rounded Bottom



Slanted Top, Flat Bottom

Technical Parameter

Diameter		Options	Heigh	
inch	mm		inch	mm
2 3/8	60.33	Perforated Hole Size from 3/32" , 1/8" to 1/2"	6	152.40
2 15/16	74.61		4 11/32	110.33
3 3/8	85.73		9	228.60
3 17/32	89.69		7	177.80
3 13/16	96.84	Wire Mesh Size from 20 mesh, 40 mesh, 60 mesh to 400 mesh	5 1/2	139.70
4	101.60		10	254.00
4 1/8	104.78		10 1/2	266.70
4 11/32	110.33		9 27/32	250.03
5 1/2	139.70		11 13/32	289.72
6	152.40		14	355.60
6 7/8	174.63		12	304.80
7 3/8	187.33		27 11/32	694.53
7 7/8	200.03		14 3/16	360.36
9 1/16	230.19		16 17/32	419.89
13 25/32	350.04		19 9/32	489.74

Technical Parameter

Diameter		Options	Heigh	
inch	mm		inch	mm
4	101.60	Perforated Hole Size from 3/32" , 1/8" to 1/2"	6	152.40
4	101.60		12	304.80
7	177.80		15	381.00
7	177.80		30	762.00

Technical Parameter

Diameter		Options	Heigh	
inch	mm		inch	mm
4	101.60	Perforated Hole Size from 3/32" , 1/8" to 1/2"	4 1/2 x 9	114.30 x 228.60
4 3/4	120.65		5 x 13 13/16	127.00 x 350.84
7 3/4	196.85		8 x 14 11/32	203.20 x 364.33
8	203.20		7 x 14 3/4	177.80 x 374.65
8 5/8	219.08	Wire Mesh Size from 20 mesh, 40 mesh, 60 mesh to 400 mesh	8 5/8 x 23	219.08 x 584.20
11	279.40		16 1/8 x 26 3/4	409.58 x 679.45
16 1/4	412.75		31 1/8 x 40 1/2	790.58 x 1028.70
24	609.60		17 1/8 x 42	434.98 x 1066.80

Flat Top, Flat Bottom				
Diameter		Options	Heigh	
inch	mm		inch	mm
15	381.00	Perforated Hole Size from 3/32" , 1/8" to 1/2" Wire Mesh Size from 20 mesh, 40 mesh, 60 mesh to 400 mesh	21 21/32	550.07
16 5/32	410.37		22 1/2	571.50
17 23/32	450.06		25 19/32	650.08
20 3/32	510.38		29 29/32	759.62
21 21/32	550.07		28 11/32	719.93
24 13/16	630.24		33 27/32	859.63
17 23/32	450.00		28 11/32	719.93
20 3/32	510.00		43 5/16	1100.14
21 21/32	550.00		30 23/32	780.26
24 13/16	630.00		4 11/32	110.33