




Temporary Basket Strainers Specification

When ordering, please specify:

1. Pipeline Size
2. Inside Diameter
3. Outside Diameter
4. Bottom Diameter
5. Length



Temporary Basket Strainers

Technical Parameter

Pipeine Size DN (inch)	Flange Dimensions (Inch)						Bottom Dia. (inch)	Length (Inch)			
	Inside Diameter	Outside Diameter (ASME Class 150 - 1500)						100%OA	150%OA	200%OA	300%OA
		150 lb.	300 lb.	600 lb.	900 lb.	1500 lb.					
3/4	5/8	2 1/8	2 1/2	2 1/2	2 5/8	2 5/8	3/8	1 1/2	-	-	4
1	3/4	2 1/2	2 3/4	2 3/4	3	3	1/2	1 1/2	-	-	4
1 1/2	1 1/4	3 1/8	3 1/2	3 1/2	3 3/4	3 3/4	3/4	2	-	3 1/2	5
2	1 3/4	3 7/8	4 1/8	4 1/8	5 1/2	5 1/2	1	2 1/2	-	4	6
2 1/2	2 1/4	4 5/8	4 7/8	4 7/8	6 3/8	6 3/8	1 1/4	2 1/2	-	4 1/2	6
3	2 3/4	5 1/8	5 5/8	5 5/8	6 1/2	6 3/4	1 1/2	3	4	5 1/2	8
4	3 1/2	5 5/8	6 7/8	7 3/8	8	8 1/8	2	4	5	7	11
5	4 5/8	7 1/2	8 1/4	9 1/4	9 5/8	9 7/8	2 1/2	5	6 1/2	9	14
6	5 1/2	8 1/2	9 5/8	10 1/4	11 1/4	11	3	5 1/2	8	11	17
8	7 1/8	10 3/4	11 7/8	12 3/4	14	13 3/4	4	7	11	14	21
10	9	13 1/8	14	15 1/2	17	17	5	8	13	17	26
12	10 7/8	15 7/8	16 3/8	17 3/4	19 1/2	20 3/8	6	10	15	20	31
14	12 5/8	17 1/2	18 7/8	19 1/8	20 3/4	22 5/8	7	10	16	22	33
16	14 1/4	20	21	22	22 1/2	-	8	12	19	24	37

Pipeine Size DN (inch)	Flange Dimensions (Inch)						Length (Inch)				
	Inside Diameter	Outside Diameter (ASME Class 150 - 1500)						100%OA	150%OA	200%OA	300%OA
		150 lb.	300 lb.	600 lb.	900 lb.	1500 lb.					
18	16 3/8	21 3/8	23 1/4	23 7/8	25	-	9	14	21	27	41
20	18 3/8	23 5/8	25 1/2	26 5/8	-	-	10	16	24	31	48
24	22 3/8	28	30 1/4	30 7/8	-	-	12	18	28	37	57
30	28 1/2	34 1/4	37 1/8	37 3/4	-	-	15	22	34	46	71
36	33	40 7/8	43 5/8	44 1/8	-	-	18	27	42	58	85